

**Description**

Oscrete 758 Water Repellent is an admixture specifically formulated to reduce the permeability of concrete, particularly where dry and semi-dry mixes are used. It is used in plastic concretes and mortars, such as for masonry work, rendering and bricklaying.

Oscrete 758 Water Repellent is based upon a carefully selected blend of solubilised carboxylic acids which form a permanent hydrophobic layer at all air-concrete interfaces within the concrete pore matrix.

**Application**

Oscrete 758 Water Repellent is suitable for use with all types of Portland Cement. It is effective in a wide range of concrete including open textured, lightweight blocks, paving, block paving and provides some water resistant properties to hardened mortars and renders.

**Standards**

Oscrete 758 Water Repellent complies with the requirements of BS EN 934-2, Table 9, for Water Resisting Admixtures.

All Christeyns products are produced in accordance with the ISO 9001:2000 Quality Management Standard and the ISO 14001 Environmental Management Standard.

**Addition Rates**

Usage rates will depend upon type of mix and desired effect, but typically:-

250 - 1000 mls per 50kg cement  
(0.5 - 2% by weight of cement)

Oscrete 758 Water Repellent should be added undiluted to the concrete mix at the same time or immediately after the mix water.



OSCRETE 758 WATER REPELLENT is an admixture specifically formulated to reduce the permeability of concrete, particularly where dry and semi-dry mixes are used. It is also used in plastic concretes and mortars, such as for masonry work, rendering and bricklaying.

### Typical Properties

#### Nature

Aqueous solution of solubilised carboxylic acids

#### Appearance

Clear Amber/Pale Straw liquid

#### Relative Density

1.03 gcm<sup>-3</sup> at 20°C

#### Air Entrainment

Less than 1% additional air entrained in dry and semi dry mixes

#### Water Soluble Chloride to EN 480-10

Less than 0.005%

#### Alkali Content to EN 480-12

3.5 % as Na<sub>2</sub>O equivalent

#### Corrosion Behaviour

No performance determined

#### Stability

Avoid freezing

#### Compatibility

Compatible with all types of Portland Cement. In accordance with BS 4721, Oscrete 758 Water Repellent will have no adverse effect on the durability or appearance of the mortar, nor on any adjacent material or component.

### Storage

Protect from extremes of temperature.

Oscrete 758 Water Repellent has a minimum shelf life of 1 year under normal conditions of storage.

### Handling

Oscrete 758 Water Repellent is a non-hazardous material but in line with general chemical handling precautions to avoid contact with skin or eyes, protective gloves and goggles should be worn.

Refer to the Material Safety Data Sheet for Oscrete 758 Water Repellent for full details.

### Packaging

200kg drums, 1000 litre IBCs and bulk deliveries.

#### Disclaimer

The physical properties quoted are typical, and should not be taken as a specification. The information supplied in our literature is based on data and experience and is given in good faith. Our policy is one of continuous research and development and we reserve the right to update this information at any time; customers should therefore ensure they have the latest issue. Whilst we guarantee the consistent high quality of our products, we have no control over the circumstances in which our materials are used, site conditions or the execution of the work and are therefore unable to accept any liability for any loss or damage which may arise as a result thereof. Materials are supplied in accordance with our standard conditions of sale.

**OSCRETE is a division of Christeyns UK Ltd.**  
Rutland Street  
Bradford  
West Yorkshire  
BD4 7EA  
United Kingdom

**Telephone: +44 (0)1274 393286**

**Fax: +44 (0)1274 309143**

**e-mail: [info@oscrete.co.uk](mailto:info@oscrete.co.uk)**

**Website: [www.oscrete.co.uk](http://www.oscrete.co.uk)**