

Description

Oscrete Betoclean is a solvent-free protective agent based on mineral oils. Oscrete Betoclean creates a film, which bonds to and protects iron and steelwork.

Application

Oscrete Betoclean is a ready-to-use product and should be applied in a thin film, preferably on a dry surface. Oscrete Betoclean prevents the adhesion of coating residue to the walls of coating booths.

Oscrete Betoclean also prevents the adhesion of concrete residue to mixers, truck-mixers, etc. After the work has been completed, the coating/concrete residue can simply be removed with a power washer, compressed air or steel brushes.

Oscrete Betoclean contains no harmful acids and does not damage paint.

Oscrete Betoclean is only suitable for use as a protective agent. It is not appropriate for form stripping, release agent or oil for general purpose use.

Oscrete Betoclean can also be used to protect unused moulds against corrosion.

Standards

All Christeyns products are produced in accordance with the ISO 9001:2000 Quality Management Standard and the ISO 14001 Environmental Management Standard.

Coverage Rates

Oscrete Betoclean is applied in a thin film. For good protection, at least 1 litre of Oscrete Betoclean should be used per 25 square metres. If an excessive dose is added to a concrete mixer, the first concrete mix produced may be damaged.



|O|S|C|R|E|T|E|

betoclean

OSCRETE BETOCLEAN is a solvent-free protective agent based on mineral oils. Oscrete Betoclean creates a film, which bonds to and protects iron and steelwork.

If necessary, Oscrete Betoclean can be thinned with a solvent.

Instructions for Use

Oscrete Betoclean can be applied with a brush, roller or sprayer. When using spraying equipment, allow for sufficient ventilation.

Typical Properties

Appearance

Light brown liquid.

Relative Density

0.86 to 0.88 at 20°C.

Flash Point

Greater than 255°C

Freezing Point

0°C

Viscosity

29 to 35 mPas at 25°C

Storage

Oscrete Betoclean thickens at low temperatures. For this reason, it is desirable to store the product in a frost-free place.

Oscrete Betoclean is not biodegradable. Please dispose of in accordance with regulations for mineral oils.

Health & Safety

Refer to the Material Safety Data Sheet for Oscrete Betoclean for full details.

Packaging

Oscrete Betoclean can be supplied in:

- Bulk, from 1000 litres
- 1000 litre containers
- Barrels of 200 litres

Disclaimer

The physical properties quoted are typical, and should not be taken as a specification. The information supplied in our literature is based on data and experience and is given in good faith. Our policy is one of continuous research and development and we reserve the right to update this information at any time; customers should therefore ensure they have the latest issue. Whilst we guarantee the consistent high quality of our products, we have no control over the circumstances in which our materials are used, site conditions or the execution of the work and are therefore unable to accept any liability for any loss or damage which may arise as a result thereof. Materials are supplied in accordance with our standard conditions of sale.

OSCRETE is a division of Christeyns UK Ltd.
Rutland Street
Bradford
West Yorkshire
BD4 7EA
United Kingdom

Telephone: +44 (0)1274 393286

Fax: +44 (0)1274 309143

e-mail: info@oscrete.co.uk

Website: www.oscrete.co.uk