

|O|S|C|R|E|T|E|

release agent

OSCRETE RELEASE AGENT is a chemical release agent for concrete designed to give optimum performance with all types of moulds and formwork.

Description

Oscrete Release Agent is a chemical release agent for concrete designed to give optimum performance with all types of moulds and formwork. It may also be used to protect machinery, mixers, hoppers, etc., to prevent build-up of mortar and facilitate cleaning.

Application

Oscrete Release Agent should be used neat and applied as thinly and evenly as possible. It can be applied by all normal methods such as spray, brush, roller etc. - any excess material should be removed. Application should always be carried out in well ventilated areas.

Benefits

- Quick and easy release of formwork
- Reduced damage to concrete and formwork
- Suitable for metal, wood, plastic and rubber moulds
- Economical coverage rates
- Improved surface finish
- Non staining
- Rust inhibition
- Protection of machinery
- Ease of cleaning

Standards

All Christeyns products are produced in accordance with the ISO 9001:2000 Quality Management Standard and the ISO 14001 Environmental Management Standard.

Coverage

Depending on the type and condition of formwork, coverage of 25 m² to 60 m² per litre can be achieved. New timber should be pre-treated, followed by a further coat prior to use.



|O|S|C|R|E|T|E|

construction products

OSCRETE

release agent

OSCRETE RELEASE AGENT is a chemical release agent for concrete designed to give optimum performance with all types of moulds and formwork.

Typical Properties

Appearance

Clear Yellow Liquid

Relative Density

0.88 at 15°C

Storage

No specific storage conditions are required but it is advisable to keep all materials in a dry area. Shelf life is indefinite in manufacturers sealed containers.

Health and Safety

Oscrete Release Agent is a non-hazardous material but in line with general chemical handling precautions to avoid contact with skin or eyes, protective gloves and goggles should be worn and inhalation should be avoided.

When spraying respiratory protection should be used.

Refer to the Material Safety Data Sheet for Oscrete Release Agent for full details.

Packaging

200 litre and 1000 litre containers, and bulk delivery.

Disclaimer

The physical properties quoted are typical, and should not be taken as a specification. The information supplied in our literature is based on data and experience and is given in good faith. Our policy is one of continuous research and development and we reserve the right to update this information at any time; customers should therefore ensure they have the latest issue. Whilst we guarantee the consistent high quality of our products, we have no control over the circumstances in which our materials are used, site conditions or the execution of the work and are therefore unable to accept any liability for any loss or damage which may arise as a result thereof. Materials are supplied in accordance with our standard conditions of sale.

OSCRETE is a division of Christeyns UK Ltd.
Rutland Street
Bradford
West Yorkshire
BD4 7EA
United Kingdom

Telephone: +44 (0)1274 393286

Fax: +44 (0)1274 309143

e-mail: info@oscrete.co.uk

Website: www.oscrete.co.uk